

ELMORE



MOBILE CRUSHING SCREENING PLANT HIRE

- 2018 Terex Finlay **JAW CRUSHER** - J-1175
- 2017 Terex Finlay **SCREEN** 693+ Supertrak
- 2015 Terex Pegson **CONE CRUSHER** - 1300 MAXTRAK
- 2 X 2018 Telestack **WHEELED STACKERS** - LS-6036H
- 1 X 2018 Telestack **WHEELED STACKER** - LS-5032H.

- **200,000 ton per month capacity** (material dependant)
- Regular Plant Maintenance by inhouse fitters
- Wet or Dry Hire
- Currently located in Western Australia (Muehea).



Call – **(08) 6323 2310**

Email- **info@elmoreltd.com.au**

ELMORE

Terex Finlay **JAW CRUSHER - J-1175**

Standard Features

- Caterpillar C9 261kW (350HP) diesel water cooled engine
- 9m³ hopper capacity c/w hydraulic folding hopper wings
- Terex 1070mm x 762mm (42" x 30") single toggle jaw chamber
- Reversible operation of jaw for clearing blockages
- 1000mm wide main conveyor belt fitted with impact bars at feed point
- Unit piped for dust suppression c/w spray bars
- Heavy duty undercarriage unit with 500mm wide track pads
- Handheld track control set c/w connection lead
- Emergency stops fitted.

Terex Pegson

CONE CRUSHER - 1300 MAXTRAK

Standard Features

- Caterpillar C13 327 kW (438hp) water cooled diesel engine
- Terex 1300 cone chamber (51" head section)
- 7m³ feed hopper with 3.5m length
- 1000mm wide main conveyor
- Metal detector fitted to feed conveyor
- Heavy Duty Undercarriage Unit with 500mm Wide Tracks
- Emergency Stops
- Piped for Dust Suppression.

Terex Finlay **SUPERTRAK 693+**

Standard Features

- Caterpillar C4.4 Acert water cooled diesel engine
- 1200mm wide variable speed belt feeder
- 4.25m wide hopper with 8.0m³ capacity
- 20' x 5' double deck screen box (6.1m x 1.52m)
- 1200mm wide plain belt on main conveyor
- 1200mm wide fines belt
- 800mm wide chevron belt on both side conveyors.

Telestack **WHEELED STACKER LS-5032H**

Standard Features

- 800mm (32") 2ply conveyor belt
- Radial Wheels to increase stockpile capacity
- Coupling ports on conveyor frame for connection to external hydraulic supply
- Troughing roller sets - 102mm Diameter
- Disc return rollers - 150mm Diameter
- Telescopic frame completes with hydraulic ram for height adjustment
- Single drive orbital motor driving head drum.

Telestack **WHEELED STACKER LS-6036H**

Standard Features

- 900mm (36") 2ply conveyor belt
- Radial Wheels to increase stockpile capacity
- Coupling ports on conveyor frame for connection to external hydraulic supply
- Troughing roller sets - 102mm diameter
- Disc return rollers - 120mm diameter
- Telescopic frame completes with hydraulic ram for height adjustment
- Single drive orbital motor driving head drum.